



RATIO	M.A.	C.O.G.			MAX OUTPUT TORQUE Nm (lbs.ft)
		X	Y	Z	
4	3.40	0	68	47	4067 (3000)
6	5.10	0	66	45	4067 (3000)

MAX BORE SQ KEY			MAX BORE RECTANGULAR KEY			MAX STEM SCREW ACCEPTANCE DIA 100 (3.875")
STD	BORE	KEY	STD	BORE	KEY	
BS4235	-	-	BS4235	96.0	28x16	
BS46	3.500"	7/8" SQ	BS46	3.625"	1"x3/4"	
ANSI B17.1	3.500"	7/8" SQ	ANSI B17.1	3.625"	7/8"x5/8"	

	INPUT FLANGE DETAILS					
	FLANGE	SHAFT	RECESS	RECESS	HOLE DETAILS	KEY
	O/DIA. & THICKNESS	DIA.	DIA.	DEPTH	22.5"(OFF CENTRES)	DETAILS
ISO F25	Ø300 x 20	Ø50.00-0.05	Ø200.10+0.10	5	8 HOLES Ø16.5 (Ø0.65")	14x9x55
	(Ø11.81" x 0.79")	(Ø1.969"-0.002")	(Ø7.878"+0.004")	(0.20")	ØN Ø254.0 (Ø10.00") P.C.	(0.55"x0.35"x2.17")
FA25	Ø300 x 20	Ø50.00-0.05	Ø152.37+0.10	5	8 HOLES Ø16.5 (Ø0.65")	14x9x55
	(Ø11.81" x 0.79")	(Ø1.969"-0.002")	(Ø5.999"+0.004")	(0.20")	ØN Ø254.0 (Ø10.00") P.C.	(0.55"x0.35"x2.17")

	BASEPLATE DETAILS	
	SPIGOT DIA.	HOLE DETAILS (22.5" OFF CENTRES)
ISO F30	Ø229.95-0.05	8 HOLES M20x25 (0.98") DEEP
	(Ø9.053"-0.002")	ØN Ø298.0 (Ø11.73") P.C.
FA30	Ø177.70-0.05	8 HOLES 3/4"UNCx25 (0.98") DEEP
	(Ø6.996"-0.002")	ØN Ø298.5 (Ø11.75") P.C.

**rotork  
gears**

**IB11 GEARBOX  
F25/FA25 INPUT F30/FA30 OUTPUT**

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT [www.rotork.com](http://www.rotork.com)

APPROX WEIGHT 119.1 kg

DRAWING No	PUBIB11-F25-F30	Regina House Ring Road Bramley Leeds LS134ET United Kingdom
ISSUE	01	
DATE	11/05/2011	