


\*\* Maximum available dimensions acc iso 5211

**DESCRIPTION**  
 Travel : -5° to 95° adjustment  
 Ratio : 40 : 1  
 Turns to Close : 10  
 Weight : 5.4 Kg (11.91lb) Excl Handwheel

**MOUNTINGHOLES**  
 Bolt Circle : Min. Ø 102 [4.02] | Max. Ø 140 [5.51] |  
 Acc. ISO 5211 : F10 - F12/F14  
 Bore : Min. Ø16 [0.63] - Max. Ø44 [1.73]

**TORQUE**  
 Max. Output : 1000 Nm 8800 lbf.in.)  
 Max. Input : 83 Nm 730.4 lbf.in.)  
 M.A. : 12 ±10%



**rotork-gears**

Nijverheidstraat 25  
 7581 PV Loosdrecht  
 The Netherlands

**Gearbox 232-13 F10-F12/F14(prepar. for insert)**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS

Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-13

Rev.: 00

Contents Subject to change without notice.