		1		2		3		4		5		6		
A	INPUT FLANGE DETAILS						MOUNTING		DUNTING HOLES - BOL	NG HOLES - BOLT CIRCLE (OFF CENTRES)			STE	
	INPUT FLANGE	Flange o/dia.	SHAFT DIA.	RECESS DIA.	RECESS DEPTH	HOLE DETAILS (OFF CENTRES)	KEY DETAIL	S ISO 5211 / MSS SP-101 MOUNTING OPTION	HOLE DETAILS (OFF CENTRES)	MAX OUTSIDE DIA. INCLUDING DRILLED HOLES	MIN INSIDE DIA. INCLUDING DRILLED HOLES	SQ BORE MAX	STANDARD	
	ISO F10	10 Ø125 x 10	Ø20.00-0.05 (Ø0.787"-0.002")	Ø70.05+0.15 (Ø2.758"+0.006")	- 4 (0.16")	4 x Ø10.5 ON Ø102.0 P.C. (4 x Ø0.41" ON Ø4.02" P.C.)	6x6x40 (0.24"x0.24"x1.57")	ISO F10*	4 x M10 x 16 (0.63") DEEP ON Ø102.0 (Ø4.02") P.C.	– Ø150 (5.90")	Ø101 (3.98")	□ 51 (2.01") -	BS4235 BS46	
	FA10	(Ø4.92" x 0.394")		Ø58.70+0.15 (Ø2.311"+0.006")				57") FA10*	4 x 3/8" UNC x 16 (0.63") DEEP ON Ø102.0 (Ø4.02") P.C.				ANSI B17.1 DIN 6885	



